


DOT R DIRECT




PERFORMANCE

- Up to 90lm/W
- CRI > 90
- 900lm/9W output




MOUNTING

Surface




Pendant





DIMENSIONS

SURFACE
direct



PENDANT
direct



5 YEAR
limited
led warranty

Catalog Number Example

DOTR-SUR-WH-1L-27K-C90-NOACC-SP-R19D-UNV-010V-1500LM-FTCA

A RANGE

DOT-R _____ DOT R

H ACCESSORIES

No Accessory _____ NOACC
Honeycomb Louver _____ HCOMB

B MOUNTING

Surface _____ SUR
Pendant _____ PDT

I VOLTAGE

120V / 277V _____ UNV

C COLOR

White _____ WH
Black _____ BL

J DIMMING

0-10V 1% _____ 010V
Hi-lume 1% EcoSystem _____ LDE1

D COLOR (HARDWARE)

White _____ WH
Black _____ BL

K OUTPUT PER LAMP

1000lm 11W 1000LM - 11W
1500lm 16W 1500LM - 16W
1900lm 20W 1900LM - 20W

E CCT

2700 K _____ 27K
3000 K _____ 30K
3500 K _____ 35K
4000 K _____ 40K

L CANOPY TYPE

Flat canopy _____ FTCA

F CRI

CRI > 80 _____ C80
CRI > 90 _____ C90

G REFLECTOR

Spot 19° _____ SP - R19D
Medium 26° _____ MD - R26D
Flood 37° _____ FL - R37D
Wide flood 62° _____ WI - R62D

BASO
basolighting.com
xalusa.com